Q M SYSTEMS CORP. *

Factory: 2077 N. E. 154 Street North Miami Beach, Florida 33162

Certificate of Verification

Chis is to certify that: STANDARDIZED AND CERTIFIED BRINELL TEST BAR NO. <u>3471</u> has been calibrated in the Standardizing Laboratory of Q M SYSTEMS * in accordance with Part C of Standard Method Test for Brinell Hardness of Metallic Materials, A. S. T. M. Designation E - 10, Sections 13 through 21 and has been found to have a hardness of <u>250</u>

10.0 / 3000

The applied loads were verified with Morehouse Proving Ring No. <u>2683</u> and SERVICE Proving Ring No <u>70044</u> The measurement of diameter of impression was read with a measuring microscope graduated to read <u>.002mm</u> and verified by Bausch & Lomb Micrometer Stage No. <u>311699</u> traceable to the Nacional Bureau of Standards and by Optical Grating No. <u>25142</u> manufactured and verified by the Nobel Institute of Sweden.

Each test impression was checked by two observers. All "SERVICE" test bars are manufactured by Q M SYSTEMS * and calibrated in strict accordance with ASTM - E10 Standard Methods of Test for BRINELL HARDNESS at the SERVICE STANDARDIZING LABORATORY in Miami, Florida.

Special "SERVICE" standardizing hardness testing machine have verification tolerance considerably more rigorous than for machines used for referee, laboratory, routine, or everyday production inspection Brinell testing.

There is no absolute Standard of hardness and there is no metal perfectly homogeneous. Bars shall never be reground after being used.

Tests should be made at a regular spacing but not too close together or erratic reading due to work hardening will result. These special STANDARDIZING machines used for manufacturing "SERVICE" test bars provide separete verification of load application, penetrator, and the diameter measuring device followed by a performance test. The applied loads are checked by the use of an elastic proving device in the manner described in ASTM Methods E-4, Verification of Testing Machines, with procedures traceable to National Bureau of Standards.

Each "SERVICE" test bar is specially prepared and heat treated to give the necessary homogeneity and stability of structure; and the surfaces have a fine ground finish. Each "SERVICE" test bar is marked with the arithmetic mean of the hardness values found in the standardization test; stamped with the name "QMS" and serial number.

Date: 06 - 15 - 97 Miami Florida ATTEST:

Q M SYSTEMS CORP. *